

<b>Gas Fireplaces</b>	<b>SS = Steady State Efficiency</b>			<b>Framing</b>	<b>Framing</b>	<b>Framing</b>				
<b>Model</b>	<b>BTU's</b>	<b>Low BTU's</b>	<b>Efficiency</b>	<b>Height "</b>	<b>Width"</b>	<b>Depth"</b>	<b>H" View</b>	<b>W" View</b>	<b>Venting</b>	<b>Pwr Vent</b>
Ravelle 30	30,000	20,000	82-86% SS	41"	41 1/2"	21"	24 1/4"	33"	4 x 6 5/8"	N/A
Ravelle 42	42,000	29,500	83-86% SS	48"	44 1/2"	21"	30"	38 1/4"	4 x 6 5/8"	N/A
Adagio	13,000	10,000	71.82% SS	40 1/4"	22 1/8"	15 3/4"	20 3/4"	14 3/4"	4.5" x 7.5"	N/A
Symmetry 35	33,000	21,500	65.2%	40 5/16"	35 9/16"	21 7/16"	25 5/8"	29 1/8"	4.5" x 7.5"	N/A
Symmetry 40	37,000	23,500	64.6%	40 5/16"	40 9/16"	21 7/16"	25 5/8"	34 1/8"	4.5" x 7.5"	N/A
Symmetry 45	39,000	26,000	66.2%	40 5/16"	45 9/16"	21 7/16"	25 5/8"	39 1/8"	4.5" x 7.5"	N/A
Montebello 40 (LS40)	51,800	40,500	35% (P4)	43"	50 3/4"	25 1/4"	29 9/32"	34 3/4"	8" x 11"	4.5" x 7.5"
Montebello 45 (LS45)	60,400	47,500	50.8% (P4)	48"	56 7/8"	25 1/4"	34 1/2"	40 59/64"	8" x 11"	4.5" x 7.5"
Montebello ST (LSM40T)	60,000	40,000	68%	47 5/16"	52 1/6"	26 5/16"	29 19/32"	34 3/4"	8" x 11"	4.5" x 7.5"
Spectra 35 (LSS-35)	33,000	23,500	70%	42 5/8"	35 1/8"	20 13/16"	17 1/2"	28"	4.5" x 7.5"	N/A
Spectra 40 (LSS-40)	41,500	28,400	70%	44 1/8"	40 1/8"	20 13/16"	19"	33"	4.5" x 7.5"	N/A
EDV3530 (* Millivolt Only)	27,000	21,000*	63%	40 1/2"	35 1/2"	22 1/4"	21"	29 1/2"	4.5" x 7.5"	N/A
EDV4035 (* Millivolt Only)	30,000	23,500*	64%	40 1/2"	40 1/2"	22 1/4"	21"	34 1/2"	4.5" x 7.5"	N/A
EDV4540 (* Millivolt Only)	33,000	26,000*	65%	40 1/2"	45 1/2"	22 1/4"	21"	39 1/2"	4.5" x 7.5"	N/A
ELDV35 (* Millivolt Only)	27,000	21,000*	66%	40 1/2"	36"	21 1/2"	25 5/8"	29 1/8"	4.5" x 7.5"	4.5" x 7.5"
ELDV40 (* Millivolt Only)	29,000	23,000*	66%	40 1/2"	41"	21 1/2"	25 5/8"	34 1/8"	4.5" x 7.5"	4.5" x 7.5"
ELDV45 (* Millivolt Only)	30,000	23,000*	65%	40 1/2"	46"	21 1/2"	25 5/8"	39 1/8"	4.5" x 7.5"	4.5" x 7.5"
EDVST (See-Through) *MV	39,000	31,000*	68%	46"	48 1/2"	22 3/4"	20 5/8"	34 1/2"	4.5" x 7.5"	N/A
EDVPF (Peninsula) *MV	39,000	31,000*	68%	46"	43 5/8"	22 3/4"	20 5/8"	34 1/2"	4.5" x 7.5"	N/A
EDVCR/Cl (Corner Right/Left)	39,000	31,000*	67%	46"	43 5/8"	24"	20 5/8"	34 1/2"	4.5" x 7.5"	N/A
MPD3328T (Top Vent)	17,500	11,700*	62%	33 1/4"	33 1/4"	13"	17"	27 1/2"	4.5" x 7.5"	N/A
MPD3328R (* Millivolt Only)	17,500	11,700*	61%	33 1/4"	33 1/4"	13"	17"	27 1/2"	4.5" x 7.5"	N/A
MPD3530 (* Millivolt Only)	20,000	12,800*	62%	35 1/3"	35 1/3"	16"	19"	29 1/2"	4.5" x 7.5"	N/A
MPD4035 (* Millivolt Only)	27,000	18,500*	67%	40 1/4"	40 1/4"	16"	24"	34 1/2"	4.5" x 7.5"	N/A
MPD4540 (* Millivolt Only)	29,000	20,500*	67%	40 1/4"	45 1/4"	16"	24"	39 1/2"	4.5" x 7.5"	N/A
MLDVT30 (* Millivolt Only)	13,500	10,500*	57%	35 1/4"	30 1/4"	16"	20 1/4"	24 1/4"	4.5" x 7.5"	N/A
MLDVT35 (* Millivolt Only)	16,000	12,750*	59%	35 1/4"	35 1/4"	16"	20 1/4"	29 1/4"	4.5" x 7.5"	N/A
MLDVT40 (* Millivolt Only)	20,000	15,500*	62%	40 1/4"	40 1/4"	16"	25 1/4"	34 1/4"	4.5" x 7.5"	N/A
MLDVT45 (* Millivolt Only)	23,000	17,500*	64%	40 1/4"	45 1/4"	16"	25 1/4"	39 1/4"	4.5" x 7.5"	N/A
MLDVTCD (Contemporary)EI	14,500	11,500*	56%SS	35 1/4"	35 1/4"	16"	20 1/4"	29 1/4"	4.5" x 7.5"	N/A
MPDST (See Through) *MV	30,000	23,000*	65%	35 1/4"	39 7/8"	20 3/4"	19"	29 1/2"	4.5" x 7.5"	N/A
MPDPF (Peninsula) *MV	30,000	23,000*	65%	35 1/4"	38 3/4"	20 3/4"	19"	29 1/2"	4.5" x 7.5"	N/A

Gas Inserts					Fireplace Opening					
Model	High BTU's	Low BTU	High Eff%	Low Eff%	Height"	Front W"	Depth "	Rear W"	Pipe	Fan
Medina	25,000	17,500	64%	64%	17 1/2"	31 1/2"	16"	19"	3"	155 CFM
Ravenna33/40	40,000	33,000	65.5%	65.5%	19 1/2"	31 1/2"	16"	18"	3"	155 CFM
Shoreline 33/40	40,000	33,000	63%	61%	21 1/2"	36" Min.	16"	19 1/2"	3"	155 CFM

Gas Stoves									
Model	BTU's	Efficiency	BTU's	Efficiency	Unit H"	Unit W"	Unit D"	Pipe	Fan
Epic 33/40	40,000	63.4%	33,000	56.98%	31 1/4"	23 1/2"	16 3/4"	4 x 6 5/8"	150 CFM
Vision 25/35	35,000	62%	25,000	65.08%	32 1/2"	18 1/2"	14 7/8"	4 x 6 5/8"	150 CFM
Vintage	27,000	47%	19,500	47%	27 3/8"	22 1/2"	14 3/4"	4 x 6 5/8"	Optional
Serefina CI1500DVF	28,000	67%	17,500	67%	27 1/2"	24 1/2"	19"	4 x 6 5/8"	Optional
Serefina CI2500DVF	38,500	67%	25,50	83%	28 1/2"	30 1/2"	22"	4 x 6 5/8"	Optional

Pellet Stoves									
Model	BTU's	Efficiency	GPH	Flue	Unit H"	Unit W"	Unit D"	Hopper	Fan
Bella Stove	43,000	80%	1.01 GPH	3" or 4"	34"	24 7/8"	20 1/2"	75#	150 CFM
Winslow Stove	39,500	87.3%	1.14 GPH	3" or 4"	31"	26 1/4"	23 1/4"	60#	150 CFM
Winslow Insert	37,800	87.3%	1.14 GPH	3" or 4"	23 3/8"	26 1/4"	15 1/4"	55-40#	150 CFM
Montage	32,000	88%	4.03 GPH	3" or 4"	28 11/16"	22 1/2"	23 1/8"	50#	150 CFM
Cascade	30,000	78.8%	1.3 GPH	3" or 4"	28 3/8"	23"	21 3/4"	60#	150 CFM

Wood Fireplaces * Denotes EPA Units										
Model	BTU's	Particulate	Framing	Framing	Framing	PIPE	Blower	Eff%	Box Size	Log Size
			H"	W"	D"					
Solana	N/A	3.87/2.26	43 1/4"	43 1/4"	27"	8" ASHT	Optional	40%-50%	N/A	20"
Cambria	N/A	N/A	59 3/8"	48 3/4"	28 7/8"	10" ASHT	Optional	20%-30%	N/A	20"
Ladera*	50,000	4.8 GPH	37 5/8"	35 7/8"	22"	6" ASHT	Standard	79.8%	2.0 Cu/Ft	18"
Brentood *	55,000	3.7 GPH	37"	36 3/8"	24 1/2"	6" ASHT	Optional	86.6%	2.0 Cu/Ft	19"
Brentwood LV (Longview)*	55,000	3.7 GPH	40 3/4"	36 1/4"	25"	6" ASHT	Standard	86.6%	2.0 Cu/Ft	19"
Villa Vista*	70,000	4.1 GPH	47 3/8"	38 1/4"	24 1/2"	7" ASHT	Optional	75.0%	3.8 Cu/Ft	20"
Montecito*	55,000	3.7 GPH	42"	36 1/4"	24 1/2"	6" ASHT	Standard	86.6%	2.0 Cu/Ft	19"
Montecito Estate*	80,000	7.4 GPH	49 1/2"	46 3/8"	27 3/4"	7" S-2100	Standard	86.7%	4.0 Cu/Ft	30"

**Wood Stoves**

Model	BTU's	Particulate	H"/Legs	H"/Ped	W"	PIPE	Blower	Eff%	Box Size	Log Size
Striker S160	68,000	1.6 GPH	27 1/2"	33"	23 1/2"	6" DL	Optional	78.60%	1.6 Cu/Ft	18"
Performer ST210 & SS210	76,000	4.2 GPH	30 3/8"	33 7/8"	25 1/4"	6" DL	Optional	85%	2.1 Cu Ft	20"
Grandview 230	76,000	3.6 GPH	33 1/2"	35"	25 1/8"	6" DL	Optional	84%	2.3 Cu Ft	18"
Legacy S260	79,000	4.1 GPH	33"	36 1/2"	28"	8" /6" DL	Optional	79.20%	2.6 Cu Ft	22 1/2"
Canyon ST310	84,500	3.2 GPH	38 1/2"	41 1/2"	28 1/2"	8" /6" DL	Optional	77.90%	3.1 Cu Ft	22 1/2"

**Wood Inserts**

Model	BTU's	Particulate	Front "H"	Depth	Front "W"	PIPE	Blower	Eff%	Box Size	Log Size
Striker C160	68,000	1.6 GPH	19 1/2"	12 3/4"	23 1/8"	6" DL	Optional	78.6	1.6 Cu/Ft	18"
Performer C210	76,000	4.2 GPH	19 1/4"	12 1/2"	25"	6" DL	Optional	85%	2.1 Cu Ft	20"
Legacy C260	79,000	4.1 GPH	22 3/4"	14 3/4"	28"	8" /6" DL	Optional	79.2%	2.6 Cu Ft.	22 1/2"
Elite E260	79,000	4.1 PH	22 3/4"	14 3/4"	48"	8" /6" DL	Optional	79.2%	2.6 Cu Ft.	22 1/2"
Canyon C310	84,500	3.2 GPH	22 3/4"	14 3/4"	28"	8" /6" DL	Optional	77.90%	3.1 Cu Ft	22 1/2"

**Front Open Wood Fireplaces**

Includes brick liner, grate, hidden screen pockets with mesh screens

Model	Frame H"	Frame W"	Frame D"	PIPE	View H"	View W"	DOORS	Refract	F/A Kit	Blower
LBR-3824&LBR3824H Radiant	50"	48 1/8"	25 1/2"	FTF-10	24 5/8"	38"	Opt.	Trad/HB	4" Opt.	N/A
LBR-4324&LBR4324H Radiant	50"	52 7/8"	25 1/2"	FTF-10	24 5/8"	42 3/4"	Opt.	Trad/HB	4" Opt.	N/A
RDI-36 & RDI-36-H (Radiant)	44 1/2"	43"	21 3/4"	FTF-8	20 3/16"	36"	Opt.	Trad/HB	4" Opt.	N/A
RDI-42 & RDI-42-H (Radiant)	44 1/2"	48"	24"	FTF-8	22 5/16"	41"	Opt.	Trad/HB	4" Opt.	N/A
HCI-36 & HCI-36-H Circulating	44 1/2"	43"	21 3/4"	FTF-8	20 3/16"	36"	Opt.	Trad/HB	4" Opt.	Opt.
HCI-42 & HCI-42-H Circulating	46 1/2"	48"	24"	FTF-8	22 5/16"	41"	Opt.	Trad/HB	4" Opt.	Opt.
EST-36 Estate (Radiant)	66 1/2"	48"	28 13/16"	FTF-10	29"	36"	Opt.	Required	4" Opt.	N/A
EST-42 Estate (Radiant)	66 1/2"	48"	28 13/16"	FTF-10	29"	42"	Opt.	Required	4" Opt.	N/A
EST-50 Estate (Radiant)	84 1/2"	60 3/4"	29 3/4"	FTF-13	36"	50"	Opt.	Required	4" Opt.	N/A

**Multi-View Wood Fireplaces-Radiant**

Includes brick liner, grate, mesh screens and outside air mechanism

Model	Frame H"	Frame W"	Frame D"	PIPE	View H"	View W"	DOORS	Refract	F/A Kit	Series
LS43-ST (Large See-Through)	58 5/8"	54 3/4"	26 1/4"	FTF-13	27 1/2"	52 3/4"	Required	Std	4" Opt.	DLSC
CR-3835L (Corner Left-Open)	40 5/8"	42 5/8"	24"	FTF-8	21"	38 5/8"	Opt.	Std	4" Opt.	Merit
CR-3835R (Corner Right-Open)	40 5/8"	42 5/8"	24"	FTF-8	21"	38 5/8"	Opt.	Std	4" Opt.	Merit
CST-38 (See-Through)	49"	40 1/4"	24 3/16"	FTF-8	18"	38"	Required	Std	4" Opt.	Merit
CPF-38 (Peninsula)	49"	39 1/4"	24 3/16"	FTF-8	18"	38"	Required	Std	4" Opt.	Merit

**Catalytic Vent-Free Fireplaces**

Model	Max BTU's	Min BTU's	Unit H"	Unit W"	D"	Eff %	Min Sq. Ft.	Flue	Surround
Radium (Curved Wall Mount)	8,870	5,110	27 1/4"	35 3/8"	7 1/2"	99.99%	450	Ventless	N/A
Scandium™ (Flat Wall Mount)	11,950	6,820	20 3/16"	41 1/2"	7 1/8"	99.99%	600	Ventless	N/A
Elite™ CVF (Square Mount)	6,825	3,412	27 3/16"	23 7/8"	6 1/4"	99.99%	340	Ventless	N/A
X-Fires™ 1000 Flat Wall Mt.)	8,874	5,110	25 1/4"	39 7/16"	7 1/2"	99.99%	450	Ventless	1 Req.
X-Fires™ Widescreen	11,950	6,820	25 5/8"	54 1/2"	8 5/8"	99.99%	600	Ventless	1 Req.

**Outdoor Fireplaces-Wood**

Includes all stainless steel construction, brick liner, steel grate, hidden screens,OA Kit

Model	Frame H"	Frame W"	Frame D"	PIPE	View H"	View W"	DOORS	Refract	OD Cover	Rad/Circ
Oasis™ LSO-43 & LSO43-H	50"	52 7/8"	25 5/8"	FTF-10	24 1/6"	42 3/4"	Opt.	Trad/HB	Opt.	Radiant
MP-36-OD Indoor/Outdoor	37 1/2"	41 1/2"	20 5/8"	FTF-8	20 3/16"	36"	Opt.	Standard	Opt.	Radiant
MP-42-OD Indoor/Outdoor	43 1/2"	46 1/2"	21 5/8"	FTF-8	22 5/16"	41"	Opt.	Standard	Opt.	Radiant

**Outdoor Fireplace-Gas**

Model	Frame H"	Frame W"	Frame D"	BTU'S	View H"	View W"	DOORS	Refract	OD Cover	Venting
E360DGNE & E360DGNE-H	46 1/2"	42 3/4"	20 1/2"	50,000	28 1/2"	37"	Opt.	Trad/HB	Opt.	None
E420DGNE & E420DGNE-H	46 1/2"	48 3/4"	20 1/2"	50,000	28 1/2"	43"	Opt.	Trad/HB	Opt.	None

**Lennox Shadowdance Vent-Free Gas Logs**

Log Set Model	Min "H"	Min "W"	Min "D"	Back "W"
LSVFSD-18 Log Set 18"	19"	30"	14"	20 1/2"
LSVFSD-24 Log Set 24"	19"	30"	14"	24 1/2"
LSVFSD-30 Log Set 30"	19"	38"	14"	24 1/2"

  

Burner Model	Max BTU's	Min BTU's	Grate	Millivolt	Ignition	Remote	Ember Kit
LSVFSD-NG	37,000	24,500	Yes	Yes	Piezo	Opt-Two	Optional
LSVFSD-LP	37,000	28,000	Yes	Yes	Piezo	Opt-Two	Optional

**SUPERIOR® PRODUCTS**

**Gas Fireplaces**

Model	High BTU's	Efficiency	Low BTU'S	Framing H"	Framing W"	Framing D"	H" View	W" View	Venting
SLDVT30	13,500	51%	10,000	35 1/4"	30 1/4"	16"	23 1/4"	27"	SV4.5
SLDVT35	16,000	59%	12,750	35 1/4"	35 1/4"	16"	23 1/4"	32"	SV4.5
SLDVT40	20,000	61%	15,500	40 1/4"	40 1/4"	16"	28 1/2"	37"	SV4.5
SLDVT45	23,000	59%	17,500	40 1/4"	45 1/4"	16"	28 1/4"	42"	SV4.5
SSDVST (See Through)	37,500	68%	30,000	41 7/8"	48 1/2"	22 3/4"	19"	29 1/2"	SV4.5
SSDVPF (Peninsula)	37,500	68%	30,000	41 7/8"	43 5/8"	22 3/4"	19"	29 1/2"	SV4.5

**SUPERIOR® PRODUCTS**

**Front Open Wood Fireplaces**

Includes brick liner, mesh screens & outside air mechanism

Model	Frame H"	Frame W"	Frame D"	PIPE	View H"	View W"	DOORS	Refract	F/A Kit
BR-36 & BRI-36 (Insulated)	37 1/2"	42 1/4"	20 5/8"	FTF-8	20 3/16"	36"	Opt.	Standard	4" Opt.
BR-42 & BRI-42 (Insulated)	43 1/2"	46 1/4"	21 5/8"	FTF-8	22 5/16"	41"	Opt.	Standard	4" Opt.

**Universal Vent-Free Firebox**

Includes canopy hood, brick lined back and sides & mesh draw screens. Uses VFGL 18 & 24 Logs

Model	Frame H"	Frame W"	Frame D"	Blower	View H"	View W"	DOORS	Refract	Canopy	Rad/Circ
UVF-36 Front-Open	40 1/4"	42 1/4"	20 1/2"	Opt.	24 1/2"	36"	Opt.	Standard	N/A	
UVFRC-3628 & UVFRC-3628-H	44 1/4"	42 1/4"	20 1/2"	Opt.	28"	36"	Opt.	Trad/HB	Opt.	Circ.
UVFRC-4228 & UVFRC-4228-H	44 1/4"	48 1/4"	20 1/2"	Opt.	28"	42"	Opt.	Trad/HB	Opt.	Circ.

**Vent-Free Fireplaces-Radiant**

Includes Black Firebox Interior, "Split Oak" Gas Log Set and Mesh Screens/99.99% Efficient

Model	Max BTU's	Min BTU's	Frame H"	Frame W"	Frame D"	Doors	Blower	Refractory	Surround	Trim Kit
VF-4000-2 Manual Control	25,000	14,000	37 1/4"	37"	15 1/2"	N/A	Optional	Optional	2-Opt.	Opt.
VF-4000-2 Millivolt Control	25,000	19,500	37 1/4"	37"	15 1/2"	N/A	Optional	Optional	2-Opt.	Opt.
VF-5000 Front Open Radiant	25,000	19,500	37 1/4"	37"	15 1/2"	Optional	Optional	Optional	2-Opt.	Opt.
VF-6000 Front Open Radiant	32,000	25,000	42 3/8"	41"	19 1/2"	Optional	Optional	Optional	2-Opt.	Opt.
VFST-2 See-Through Radiant	34,000	27,000	43"	43 1/4"	22 3/4"	Optional	Optional	Standard	1-Opt.	Opt.
VFPP-2 Peninsula Radiant	34,000	27,000	43"	40 1/8"	22 3/4"	Optional	Optional	N/A	1-Opt.	Opt.

**SUPERIOR® PRODUCTS**

**Superior VFGL-4/VFST27-2 Vent-Free Gas Logs** Includes Ceramic Fiber Split Oak Logs, Burner, Grate & Variable Flame Control

Log Set Model	Min "H"	Min "W"	Min "D"	Back "W"	Valve	Remote	See-Thru	Canopy	Max BTU	Min BTU
VFGL-18MSN-4 (Natural)	16"	20"	14"	19"	Manual	Optional	N/A	Optional	25,000	14,000
VFGL-18MSP-4 (L.P.)	16"	20"	14"	19"	Manual	Optional	N/A	Optional	25,000	14,000
VFGL-24MSN-4 (Natural)	16"	26"	14"	22"	Manual	Optional	N/A	Optional	32,000	17,000
VFGL-24MSP-4 (L.P.)	16"	26"	14"	22"	Manual	Optional	N/A	Optional	32,000	17,000
VFGL-28MSN-4 (Natural)	16"	30"	14"	26"	Manual	Optional	N/A	Optional	32,000	17,000
VFGL-28MSP-4 (L.P.)	16"	30"	14"	26"	Manual	Optional	N/A	Optional	32,000	17,000
VFGL-18VSN-4 (Natural)	16"	20"	14"	19"	Millivolt	Optional	N/A	Optional	25,000	19,500
VFGL-18VSP-4 (L.P.)	16"	20"	14"	19"	Millivolt	Optional	N/A	Optional	25,000	19,500
VFGL-24VSN-4 (Natural)	16"	26"	14"	22"	Millivolt	Optional	N/A	Optional	32,000	25,000
VFGL-24VSP-4 (L.P.)	16"	26"	14"	22"	Millivolt	Optional	N/A	Optional	32,000	25,000
VFGL-28VSN-4 (Natural)	16"	30"	14"	26"	Millivolt	Optional	N/A	Optional	32,000	25,000
VFGL-28VSP-4 (L.P.)	16"	30"	14"	26"	Millivolt	Optional	N/A	Optional	32,000	25,000
VFST27-VSN-2 (Natural)	18"	28"	14"	28"	Millivolt	Optional	Yes	Optional	32,000	25,000
VFST27-VSP-2 (L.P.)	18"	28"	14"	28"	Millivolt	Optional	Yes	Optional	32,000	25,000